The Nobi Ceiling Light is an AI-powered, ceiling-mounted device purpose-built to safeguard older adults and people with physical or cognitive impairments. More than just a light, it functions as a proactive care system offering 24/7 monitoring, fall detection, emergency alerts, two-way voice communication, and preventive insights, all in one sleek unit.

Product name	Nobi Ceiling Light 2.0
Model number (SKU)	144003 Desert (PANTONE 13-4403 TPG)
	144004 Slate (PANTONE 18-0201 TPG)

User experience

Environment	Indoor dry location (living room, bedroom...)
Install instructions	Scan this QR code for step-by-step instructions

Physical characteristics

Weight	Nobi Ceiling Light 2.0: 5.62 lbs / 2.55 kg Nobi Power 2.1: 0.88 lbs / 0.4 kg
IP rating	IP20
Operating temperature	50 °F to 104 °F / 10 °C to 40 °C

Dimensions

(Detection area: Ø 26 ft / 8 m)



Ceiling adapter (optional):
h 0.41 in / 10.5 mm
Ø 6.63 in /168.4 mm

Ø 8.9 in / 226 mm
h 7.55 in / 191.7 mm

h 5.39 in / 136.8 mm



Ø 15.16 in / 385 mm

Light specifications

Color temperature	LED light (2750 - 6600 K)
Brightness	984.4 lm

Technical specifications

Operating voltage	100/240 V AC (50/60 Hz)
Maximum output	24 V / 2.2 A
Power consumption	Standby: 17 W Normal: 40 W

Order information

Content	Nobi Ceiling Light 2.0 Nobi Power 2.1 Ceiling adapter 4 metric screws
EAN code	Desert: 5407011440033 Slate: 5407011440040
Contact	Nobi USA Inc. 820 Gessner Road Suite 300, Houston TX 77024, US Nobi NV Neerlandweg 16 2610 Wilrijk, BE

Connectivity & compatibility

Bluetooth	BLE 5.0
WIFI	802.11 a/b/g/n/ac
Compatibility	iOS and Android

Environment & safety

Warranty	2 years
Certifications	FCC ID N6C-SXPCEAC2 R-41268240 CE
Recycling	